

# PURE CLICK TECHNICAL DATA



Board: 1326 x 204 mm – Box: 8 boards (= 2,164 m<sup>2</sup>) – Pallet: 56 boxes (= 121,186 m<sup>2</sup>)  
 Board XXL: 1836 x 204 mm – Box: 6 boards (= 2,247 m<sup>2</sup>) – Pallet: 56 boxes (= 125,847 m<sup>2</sup>)  
 Tile: 612 x 612 mm – Box: 6 tiles (= 2,247 m<sup>2</sup>) – Pallet: 28 boxes (= 62,923 m<sup>2</sup>)  
 Tile: 612 x 306 mm – Box: 8 tiles (= 1,498 m<sup>2</sup>) – Pallet: 56 boxes (= 83,898 m<sup>2</sup>)

PRODUCT SPECIFICATION		CLICK 40	CLICK 55
Total thickness	EN 428	5 mm	5 mm
Wear layer	EN 429	0,40 mm	0,55 mm
Total weight	EN 430	6,14 kg/ m <sup>2</sup>	6,14 kg/ m <sup>2</sup>
Surface treatment		PUR	PUR
Usage classification	EN 685	23-32	23-33
<b>TEST RESULTS</b>			
Underfloor heating	EN 12524	suitable max. 27°C (80°F) / electrical floor heating systems: max 60 W/m <sup>2</sup>	
Castor chair	EN 425	pass	pass
Fire resistance	EN 13501-1	Bfl-s1	Bfl-s1
Chemical resistance	EN 423	OK	OK
Thermal resistance	ISO 8302	0,041	0,041
Residual indentation	EN 433	< 0,10 mm / 4 %	< 0,10 mm / 4 %
Slip resistance	DIN 51130 EN 13893	R11 class DS	R11 class DS
Sound reduction: Impact Sound	EN ISO 717-2 (Δ Lw)	10 dB	10 dB
Reflected Walking Sound	EPLF draft 021029-5 F1	*** (9,7 sone )	*** (9,7 sone )
Light fastness	ISO 105-B02	> 6	> 6
Dimensional stability	EN ISO 23999	<0,25%	<0,25%
Antistatic	EN 1815	yes	yes
Residential warranty		Lifetime	Lifetime
Commercial warranty		-	10 years
Formaldehyde	EN 717-1	E1	E1
RRL Pendulum test		≥ 0,36 (wet test 4S Rubber/Slider 96)	

